

Synergie Anschlusskleber AK

Universal acrylic sealant

Properties	Cartridge	Tube
Article	1179.0	1652.0
Material	Copolymer based on acrylic acid esters with additives	
Content	310 ml	600 ml
Density	Approx. 1,0 g/cm ³ (DIN EN ISO 1183-1)	
Viscosity	Pasty and thixotropic consistency (DIN EN ISO 7390)	
Skin formation (23°C, 50% RH)	Immediate adhesion, starting at about 30 minutes	
Drying time	From 1 to 7 days, depending on the surfaces porosity, the temperature and the quantity of product applied	
Average yield	Approx. 30 / 40 g/m, depending on the diameter application	
Working temperature	-5°C / +40°C	
	Recommended da +5°C	
Operating temperature	-30°C / +80°C	
Colour	Yellow	
Packaging	20 cartridges of 310 ml	20 bags of 600 ml
Storage	Cool and dry away from UV rays, max. 12 months	

Synwer GmbH reserves themselves the possibility to review or change these technical values. You can find the technical data sheet on the website www.synwer.com. This data sheet replaces the previous copy.

Synwer GmbH
Gierlichsstr. 23
53840 Troisdorf [Tel: +49 2241 397 990 0](tel:+4922413979900) www.synwer.com

Version: Juni 2020