

Synergie Repair Tape Grey

Acrylic adhesive tape with nonwoven fabric in PP

Properties	Value
Measurements	60 mm x 25 m
Color	Grey
Adhesive	Solvent and emollient free acrylic based adhesive
Adhesive backing	Nonwoven fabric in PP
Adhesive weight	210 g/m ² (DIN EN ISO 536)
Reinforcement	None
Thickness (without cover)	0,55 - 0,57 mm (DIN EN 1942)
Covering material	Silicone liner
Tear strength with elasticity	≥ 50 N/25 mm; 40% (DIN EN 14410)
Application temperature	+5°C / +30°C
Operating temperature	-30°C / +100°C
Sd value	approx. 8 m
Resistance to detachment	Passed (DIN 4108-11)
Resistance to condensation	Very high
Resistance to aging	Very high
Initial adhesion (tack)	Very high
Packaging	10 rolls
Storage	Cool and dry away from UV rays, max. 24 months
Storage temperature	+18°C / +25°C

Synwer GmbH reserves themselves the possibility to review or change these technical values. You can find the technical data sheet on the website www.synwer.com. This data sheet replaces the previous copy.

Synwer GmbH
Gierlichsstr. 23
53840 Troisdorf [Tel: +49 2241 397 990 0](tel:+4922413979900) www.synwer.com

Version: Juni 2020